



XC998

— WHEEL LOADER —

All Rights Reserved

Materials and specifications are subject to change without notice.
Featured machines in photos may include additional equipment.
See your XCMG dealer for available options.

www.xcmg.com

XCMG Regional Departments:

Europe	(+86-516) 87739703 87739218 87739537
West Asia & North Africa	(+86-516) 87739702 87739202 87739223
Asia-Pacific	(+86-516) 87739128 87739500 87739529
Africa	(+86-516) 87735009 87739222 87739283
Central Asia	(+86-516) 87739236 87739239 87739538
America	(+86-516) 87739285 87739551 87739710


XUZHOU CONSTRUCTION MACHINERY GROUP IMP. & EXP. CO., LTD

Add: No.1, Tuolanshan Road, Xuzhou Economic Developing Zone, Jiangsu, China 221004

Fax: (+86-516) 87739230

E-mail: export@xcmg.com





High efficiency and reliability Inheritance
of classic and high maturity
and stability

OVERVIEW

MODEL CHARACTERISTICS

- It features high efficiency, energy-saving, and strong power.
- The three-element torque converter and the fixed shaft power shift transmission feature high maturity and reliability.
- The 3700mm wheelbase features high mobility and flexibility and is applicable to all kinds of working sites.
- The bucket is made of high strength material to realize high wear and impact resistance.
- The diversified configurations and complete attachments adapt to the construction needs in different regions and under different working conditions.
- The optional A/C and the sound insulation and noise reduction measure build elaborately a comfortable operating environment.

XCMG'S EXCLUSIVE TECHNOLOGIC ADVANTAGES

The certified safe and comfortable ROPS/FOPS cab with ergonomic internal arrangement provides the driver with first-class operating environment

Power System:

The reasonable matching between engine and transmission guarantees faster response of machine and meanwhile reduces the machine fuel consumption by 10%.

The full-automatic power shift transmission can automatically adjust the gear of loader to guarantee the running of loader under highest efficiency and most energy-saving status.

Z-Linkage System:

The traditional Z-linkage system is in-depth optimized by XCMG to incorporate powerful force at all positions.

Intelligent Hydraulic System

The load-sensing variable hydraulic system supplies on-demand power to the steering system and various working devices to reduce fuel consumption.

Attachments:

XCMG offers diversified attachments to meet your personalized needs and promote the productivity.


The maintenance-free full-hydraulic wet type brake axle incorporates the automatic limited-slip differential function to sufficiently play the powerful insertion force of the machine.

POWER SYSTEM

XC9 series loader incorporates incomparable reliability to ensure long-time continuous working and reduce unnecessary maintenances. The long-tested drive parts and heavyweight structural parts work with more diligent detailed design to ensure that the machine is competent for more stringent working conditions.

The world's leading design means and intelligent manufacturing technologies ensure that the structural parts, including front and rear frames and attachments, meet the working needs under diversified heavy working conditions. The concise large articulated open-type heavyweight structural parts reduce the stress concentration and meet the working needs under diversified severe working conditions. The heavyweight articulated structure guarantees longer life.

This product is powered by Eu stage V compliant electronic control turbocharged engine, in which the high pressure common rail fuel supply system is controlled by ECU to achieve accurate fuel injection control, high pressure, low pressure fluctuation, optimal combustion rate, atomization, and ignition timing, high combustion efficiency, high power reserve, and strong power. This engine features the advantages of high reliability, high adaptability, low fuel consumption, and low emission.



RADIATOR SYSTEM

The single-layer radiator system with large fin spacing + rotary openable A/C radiator prevent the accumulation of material at radiator openings and meanwhile ease the maintenances. Every radiator can be replaced rapidly and independently.

The transmission and drive axle of industry's renowned brands are installed to guarantee reliable performance and durable life. The rear axle can swing for $\pm 13^\circ$ to maintain four tires on the ground, in order to keep stability on rugged roads and easily play the powerful traction force of the machine.

In response to the heavy working conditions, the boom and bucket breakout forces are optimized to promote the digging capacity by 15%. The boom and bucket can realize composite motions to further promote the working efficiency.

The selection of bucket depends on the material density and the expected bucket fullness coefficient. Thanks to the bucket design, the excellent rollback angle in all directions, and the outstanding bucket loading performance, the actual bucket capacity is generally higher than the rated capacity.

HANDLING BUCKET

The shape design of the bucket is optimized to fully fill the bucket faster and more efficiently during the digging and meanwhile achieve high fullness coefficient. The guide plates are installed on the top of the bucket to reduce the spilling of material during the lifting and meanwhile effectively protect the cab.

SHORTER WORK CYCLE TIME

The displacement of the hydraulic pump and the travel of the lifting cylinder are optimized to increase the boom lifting speed by 12% and increase the steering speed by 10%. In addition, the steering angle of the machine is increased to 40° to achieve shorter driving route and faster work cycle during the loading operations.



OPTIONAL ATTACHMENTS

XC9 series loader is provided with diversified optional attachments so that the customers can choose different attachments depending on own needs, such as gripping of lumbers, handling in quarries, earthwork loading, and material lifting. In response to the digging operation, multiple buckets are offered at the customer's choice, such as mine bucket for rocks and light material large bucket for coal or wood bits. In addition, the optional quick change structure can be installed to realize "One machine for multiple applications".

Z-LINKAGE SYSTEM

The traditional Z-Linkage System is in-depth optimized by XCMG to achieve powerful bucket breakout force and outstanding boom lifting capability at any position. The redesigned hydraulic system realizes the simultaneous tipping and lifting motion of bucket to achieve more powerful digging capacity and faster material loading of the bucket.

Depending on diversified operation needs, various high firmness and durability attachments can be installed to maximize the productivity and achieve more applications. No matter the repeated handling of material, the loading and unloading of cargo, the gripping of lumbers or steel tubes, or other application, these attachments can effectively fulfill diversified tasks and promote the efficiency.

The full-automatic power shift transmission can automatically adjust the gear of loader to guarantee the running of loader under highest efficiency and most energy-saving status.

The full-automatic power shift transmission matches reasonably with engine system. The transmission can match with the parameters, including the engine speed and machine speed, to automatically adjust the gear of loader and guarantee the running of machine under highest efficiency status. This can speed up the cycle time and reduce the fuel consumption. If the loader requires more power under complicated working condition, the operator can manually downshift to a lower gear to meet the working needs.

HIGH EFFICIENCY POWER

The machine is powered by Cummins Eu stage V electronic control turbocharged engine, in which the high pressure common rail fuel supply system is controlled by the ECU to achieve the advantages of accurate fuel injection control, high consumption efficiency, and low fuel consumption and emission.

HIGH-EFFICIENCY HYDRAULIC SYSTEM

The full-variable load-sensing hydraulic system supplies on-demand power to the hydraulic devices and steering device to eliminate energy waste and reduce fuel consumption. The powerful hydraulic system can guarantee the quick response within shorter cycle time and more stable operations by excellent control of load and attachment.

EXCELLENT POWER MATCHING

The full-automatic power shift transmission matches reasonably with engine system. The transmission can match with the parameters, including the engine speed and machine speed, to automatically adjust the gear of loader and guarantee the running of machine under highest efficiency status. This can speed up the cycle time and reduce the fuel consumption. If the loader requires more power under complicated working condition, the operator can manually downshift to a lower gear to meet the working needs.

LOW-SPEED ENERGY-SAVING RADIATOR SYSTEM

The automatic stepless-regulated low-speed radiator system can remarkably reduce the fuel consumption besides the quiet working characteristic.



We all know that the operator feeling comfortable can relieve the fatigue feeling and promote the working efficiency and operation safety. Therefore, designing an industry leading cab around the operator to provide a spacious, safe, quiet, and comfortable environment can further improve the operation safety and maintain high productivity.

SINGLE-JOYSTICK CONTROL

The optional multifunctional joystick can ease the operator's operations and meanwhile accurately control the hydraulic functions. The forward, reverse, and kick-down functions are provided on the control panel.

DRIVING STABILIZING SYSTEM

While driving on rugged roads, the optional driving stabilizing system can improve the driving stability and load retentivity. The operator can be more confident during the transfer operations at high speed to promote the productivity.



EFFICIENT

CE COMPLIANT CAB ACCESS

The driver can open the cab door by standing on the ground and then access the cab safely and conveniently via the obliquely installed ladder. The optimally arranged handrails can maintain the safe three-point contact at all times.

CAB AIR FILTER

The cab air inlet port is located on the right side of the cab and is installed with easily replaceable air filter. The fresh air is supplied into the cab after its dusts and particles are filtered out by the air filter. In addition, the air filter works with the excellent airtightness of the cab to play a slight pressurization role to further isolate the external dusts. The working environment is clean and comfortable and is comparable with the working efficiency.

With a broad vision, the cab boasts the industry's best 316.5° effective horizontal visual angle. Cab: This machine is equipped with FOPS/ROPS pressurized cab, with heating and A/C system and diaphragm molded rubber floor. Instruments: The multifunctional combination instrument centrally displays all important information within the operator's visual range. Seats: The adjustable suspension seats are fixed on the cab floor. Certification: The cab has been tested and certified as per ROPS standard (ISO 3471) and FOPS standard (ISO 3449).

The large opening hood, easily accessible pressure measurement and lubricating points, centrally arranged electric fuse case, and the machine diagnostic interface ease the daily maintenances and repairs of the machine.

First-class machine repair and maintenance access and reasonable machine layout and structural design.

LUBRICATION SYSTEM

During the running of loader, the optional automatic lubrication system controls the lubrication to provide longer running time and reduce the maintenance cycles. The operator can change the lubrication interval depending on the application.

ENGINE HOOD

The large-angle side-opening engine hood ease the maintenances of engine oil filter, diesel filter, transmission and torque converter oil filters, and air filter and meanwhile ease the cleaning of every radiator fin.

RADIATOR SYSTEM

The single-layer radiator system with large fin spacing + rotary openable A/C radiator prevent the accumulation of material at radiator openings and meanwhile ease the maintenances. Every radiator can be replaced rapidly and independently.

CENTRALIZED OIL FILLING AND DRAINAGE

The inaccessible hinge lubricating points and the engine oil/water drainage ports are centrally guided out to ease the maintenances.



STANDARD CONFIGURATION

Power System

- Automatic power shift
- Manually controlled forward/reverse changeover joystick
- Transmission oil level sight indicator
- Front axle limited-slip differential lock

Engine

- Three-stage air filter, prefilter, and primary and secondary filters
- Coolant level sight indicator
- Intake preheater
- Fuel filler filter screen
- Fuel prefilter with water separator
- Fuel filter
- Exhaust heat insulator
- External radiator air inlet protection
- Centrifugal air prefilter
- Reversible cooling fan
- Single electronic accelerator pedal
- Engine oil drainage extraction port
- Coolant drainage extraction port

Electric System

- 24V pre-wiring system for optional accessories
- 24V/75V alternator
- Fuel Gauge
- Hourmeter
- Horn (Including reversing buzzer)
- Integrated combination instrument
- Diesel level gauge
- Transmission oil temperature gauge
- Engine coolant temperature gauge
- Warning lamps and indicator lamps
- Engine oil pressure gauge
- Battery voltmeter
- Low brake pressure warning
- Engine tachometer
- Reversing camera display
- Negative switch

Lamp

- Double LED headlamp with high beam and low beam
- Double brake lamp and rear lamp
- Turn signal lamp with hazard warning lamp function
- LED working lamps (4 front and 2 rear lamps)
- Reversing warning
- Rotary warning lamp

Warning and Indicator Lamps

- Battery charging
- Parking brake

Warning and Display Information

- Engine coolant temperature
- Engine oil pressure lamp
- Transmission oil temperature
- Braking pressure (Only low pressure warning)
- Applied parking brake (Only display)

Cab

- ROPS (ISO 3471)
- FOPS (ISO 3449)
- Sound insulation lining
- Cigarette lighter
- Lockable door
- Cab A/C system and defroster with fresh air inlet
- Interior lamp
- Interior rearview mirror
- Double exterior rearview mirror
- Right sliding window
- Colored safety glass
- Adjustable steering wheel
- Storage box
- File pocket
- Front sun visor
- Front and rear windscreen washers
- Front and rear windscreen wipers
- FM radio
- Engine starter key
- Door lock key
- Acoustic material interlayer
- Upholstery
- Ashtray
- 12V power socket
- 24V power socket
- Defroster
- A/C thermostat
- Anti-skid mat
- MP3 player
- 2kg powder fire extinguisher
- Emergency escape hammer
- Air-cushioned adjustable seat
- Seat belt
- Cup holder

Hydraulic System

- Pilot control main valve
- Variable Displacement Axial Plunger Pump for Following Systems :
 - Working hydraulic system
 - Steering hydraulic system (Priority)
 - Boom lifting limit
 - Bucket automatic leveling
 - Hydraulic oil level indicator
 - Hydraulic oil cooler
 - Independent radiator
 - Forward/reverse rotation of cooling fan
 - Working device lock
 - Double-acting hydraulic cylinder
 - Working device joystick

Brake System

- Independent double-circuit service brake
- Electro-hydraulically controlled parking brake
- Single brake pedal

Optional configuration

Powertrain system

- Quick refueling system
- Turbocharger delayer
- Engine delayed flameout
- Exhaust gas injector
- Fuel preheating system

Hydraulic System

- Stabilizer module function
- Pressure relief safety cap for hydraulic oil tank
- Electro-hydraulic proportional control
- Steering system
- Power steering system

*No further information of sample contents, product structure and configuration parameters updates. There maybe some difference between sample books and material objects. Please kindly prevail.

Pressure checking

- Working system pressure diagnostic interface
- Steering system pressure diagnostic interface
- Pilot system diagnostic interface
- Transmission pressure diagnostic interface

Automatic lubrication system

- Automatic lubrication pump and controller

Other equipment

- Fender
- Safety lock handle (For transportation)
- Lifting eye
- Traction pin

Vandal Proof Lock for Following Parts

- Engine compartment
- Radiator grille

Other

- Driver's tool kit

Fire Extinguishing System

- Automatic fire extinguishing system

Anti-corrosion processes

- Heavyweight anti-corrosion coating for whole machine
- Glue sealing for electric harnesses

Tires

- Michelin tires (L-4/5)

Bucket

- Rock type
- Light material type

MAIN PARAMETERS

Items

Rated operating load	9000	kg
Bucket capacity	5.4	m ³
Machine weight	30500	kg
Dumping height	3350	mm
Dumping distance	1400	mm
Wheel base	3700	mm
Tread	2460	mm
Height of hinge at maximum lift height	4600	mm
Working height(fully lifted)	≤6400	mm
Max.breakout force	≥260	kN
Ultimate tipping load/kg(straight)	≥22438	kg
Ultimate tipping load/kg(full steering)	≥19704	kg
Hydraulic cycle time-raise	≤6.8	s
Hydraulic cycle time-down	4.4	s
Hydraulic cycle time-tilt	1.3	s
Total hydraulic cycle time	≤12.5	s
Min. turning radius over tyres(tire center)	≤6400	mm
Min. turning radius over tyres(tire outward)	≤6850	mm
Min. turning radius over tyres(bucket outward)	≤7755	mm
Articulation angle	40	°
Gradeability	≥25	°
Tyre size	29.5R25	
Overall machine dimension L×W×H	9500*3500*3770	mm
Engine Model	X12	
Emission standards	Eu stage V	
Rated Power/Speed	265/2000	kW/rpm
Peak Torque/Speed	1862/1400	N.m/rpm
Fuel Tank	500	L
Hydraulic Tank	180	L
Coolant/L	62	L
DEF tank/L	48	L
Engineoil/L	34	L
Transmission oil/L	64	L
Front and Rear axle oil/L	54/54	L
Transmission gear	4 forward 3 reverse	
Travel speed	I -gear(F/R)	6.8/6.8 km/h
	II -gear(F/R)	12/12 km/h
	III-gear(F/R)	24.5/24.5 km/h
	IV-gear(F/R)	36.2/- km/h
Front and Rear axle differential pattern	front axle differential lock	



XCMG
XC998

XC998YOUR BEST HELP

— Drive axle

maintenance-free full hydraulic wet drive axle, safe and reliable

— Transmission

automatic power shift transmission, automatically adjust the loader gear to ensure that the loader is working in the most efficient and energy-saving state

— Easy to maintain

The integral electric back-flip hood + upturnable rear baffle cover is convenient for maintenance service to overhaul the equipment.

— Tools

XCMG can provide you with a variety of tools to meet individual needs and improve production efficiency.

— Cab

FOPS&ROPS certified safe and comfortable cab with ergonomically designed interior to provide the driver with an excellent operating environment.

— Intelligent hydraulic system

load-sensing variable hydraulic system, supply on demand, automatically adjust the supply of hydraulic system capacity, reduce fuel consumption

— Excellent delivery efficiency

Through the reasonable matching of engine and transmission, the response of the whole machine is faster, and the fuel consumption of the whole machine is reduced by 10%,

— Z-Linkage System

XCMG has deeply optimized the traditional Z-Linkage for great power in any position.

